

Series 6, Built-in fridge-freezer with freezer at bottom, 177.2 x 55.8 cm, soft close flat hinge KIN86ADD0G

A ↑ G









Optional accessories

KSZGGM00 Butter box

The spacious built-in fridge-freezer with VitaFresh XXL near <0°>, No Frost and constant temperature level keeps your food fresh for longer.

- VitaFresh XXL Pro near 0°C: climate-controlled compartments lock in freshness and nutrients for longer.
- **NoFrost**: never defrost again, thanks to perfect protection from ice formation that saves time and effort.
- **High-stability door trays**: extra high and flexible for more space and stability.
- · LED lights bring a completely new lighting concept to fridges
- Eco Airflow: maintains optimal air circulation and a constant temperature level throughout the cooling area.

Technical Data Average annual energy consumption in kilowatt hour per year (kWh/a):186 kWh/annum Sum of volume of chill compartments: 184 l Airborne acoustical noise emissions :35 dB(A) re 1 pW Airborne acoustical noise emission class:B Installation type:Built-in Door panel options: Possible but accessory Width of the appliance:558 mm Depth of the product: 548 mm Min. required niche size for installation (HxWxD): 1775.0 x 560 x 550 mm Fuse protection:10 A Door hinge: Right reversible Length of electrical supply cord:230.0 cm Number of compressors:1 Number of independent cooling systems:2 Interior ventilator: No Number of Adjustable Shelves in fridge compartment (Stck): 2 Frost free system: Freezer Installation type:Integrated



Series 6, Built-in fridge-freezer with freezer at bottom, 177.2 x 55.8 cm, soft close flat hinge KIN86ADD0G

The spacious built-in fridge-freezer with VitaFresh XXL near <0°>, No Frost and constant temperature level keeps your food fresh for longer.

- Built-in fridge-freezer
- easy Installation
- Fixed hinge, SoftClosing Door dampens door movement, for smooth and effortless closure

Performance and Consumption

- EU19_EEK_D: D
- Total Volume : 260 l
- Net Fridge Volume : 184 l
- Net Freezer Volume : 76 l
- Freezing capacity 24h : 8 kg
- Annual Energy Consumption: 186 kWh/a
- Climate Class: SN-ST
- EU19_Fast freezer facility_D
- Noise Level : 35 dB , EU19_Noise emission class_D: B
- Temperature rise time : EU19_Temperature rise time_D: 11 H $\,$

Functions

- Bright interior LED fridge light in fridge section

Design features

- NO_FROST_NEU_BL, never have to defrost ever again
- Separate, electronic temperature control with LED display
- Super Cooling: automatic deactivation
- Two separate cooling circuits allow independent temperature control and prevents the transference of humidity between the fridge and freezer cavity
- Optical and accoustical
- VarioZone adaptable storage for more flexibility

Key features - Fridge section

- 4 safety glass shelves in fridge compartment of which 2 are height adjustable
- 1 removable door storage compartments.
- 3 door bins
- 1 dairy compartment in door
- Metal bottle rack
- Door shelves in fridge door: 1 large and 1 small.

Food freshness system

Freshness System

- 1 VitaFresh drawer with humidity control Fruits and vegetables retain vitamins and stay fresh for longer
- 3 freezer drawers

Dimension and installation

- Dimensions: 177.2 cm H x 55.8 cm W x 54.8 cm D
- Niche Dimensions: 177.5 cm H x 56 cm W x 55 cm D

- Right hinged door, door reversible
- Height adjustable front feet
- 220 240 V
- Length of power cord:230 cm


Key features - Freezer section


- SuperFreezing function with automatic deactivation
- 1 x ice cube tray, 3 x egg tray
- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.

Additional features



Series 6, Built-in fridge-freezer with freezer at bottom, 177.2 x 55.8 cm, soft close flat hinge KIN86ADD0G





Maximal permissible weight of the unit fronts


Fitted unit fronts that exceed the permissible weight may cause damage and result in functional impairment of the hinges $\tilde{\Delta}$ Weight $\tilde{\Delta}$: Appliance door height including hinges in mm


B: Undamped hinge, unit front in kg

C: Damped hinge, unit front in kg

D: Additional possible load in kg with heavy load kit


Α	В	С	D
1500-1750	22	22	
720-1400	19	19	B+5 / C+5
A1	15	19	
A2	15	19	






The specified unit door dimensions are valid for a door gap of 4 mm.

measurements in mm



measurements in mm Recommended gap dimensions for flat hinges



The gap dimensions recommended in the table must be adhered to in order to ensure that appliance doors do not collide with anything when they are opened, and to avoid causing damage to kitchen units.