
HGS 72S BK

12NC: F163435

GTIN (EAN) code: 5054645634354







| Product group Construction type Built-in Type of control Mechanical Type of control settings Knob Number of gas burners S Number of electric cooking zones Number of radiant plates Number of halogen plates Number of induction plates Number of electric warming zones O Number of electric warming zones O Location of control panel Basic surface material Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Qas type Methane Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type UK Gas connection N/A Width of the product Depth of the product Bion Minimum niche height O Minimum niche width S55 Niche depth Automatic programmes No | MAIN FEATURES | |
|--|---------------------------------------|------------|
| Type of control Mechanical Type of control settings Knob Number of gas burners 5 Number of electric cooking zones 0 Number of radiant plates 0 Number of halogen plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Glass Main colour of product Black Electrical connection rating (W) 0 Gas connection rating (W) 10800 Gas type Methane Current (A) 0 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type UK Gas connection Y30 Height of the product 510 Depth of the product 510 Minimum niche height 0 Minimum niche width 555 Niche depth (kg) 166 | Product group | Hob |
| Number of gas burners Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogen plates Number of induction plates Number of electric warming zones Location of control panel Basic surface material Basic surface material Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Current (A) Voltage (V) Prequency (Hz) Length of Electrical Supply Cord (cm) Plug type UK Gas connection N/A Width of the product Beight of the product 51 Depth of the product Minimum niche height Minimum niche width 555 Niche depth Net weight (kg) 10 O O O O O O O O O O O O O | Construction type | Built-in |
| Number of gas burners Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogen plates Number of induction plates Number of electric warming zones Location of control panel Basic surface material Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type Methane Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type UK Gas connection N/A Width of the product Biack Uring type UK Gas connection N/A Width of the product Depth of the product Since Mendane Since Since Since Since Minimum niche height Minimum niche width Since Minimum niche width Since Minimum niche width Since Minimum niche width Since Minimum niche width Minimum niche width Since Minimum niche width | Type of control | Mechanical |
| Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogen plates Number of induction plates Number of electric warming zones O Number of control panel Basic surface material Basic surface material Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type Methane Current (A) O Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type UK Gas connection N/A Width of the product Depth of the product S10 Minimum niche height O Minimum niche width S55 Niche depth Net weight (kg) 10 | Type of control settings | Knob |
| Number of electric plates 0 Number of radiant plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Glass Main colour of product Black Electrical connection rating (W) 0 Gas connection rating (W) 10800 Gas type Methane Current (A) 0 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type UK Gas connection N/A Width of the product 51 Depth of the product 510 Minimum niche height 0 Minimum niche width 555 Niche depth 475 Net weight (kg) 16 | Number of gas burners | 5 |
| Number of radiant plates 0 Number of halogen plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Glass Main colour of product Black Electrical connection rating (W) 0 Gas connection rating (W) 10800 Gas type Methane Current (A) 0 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type UK Gas connection N/A Width of the product 730 Height of the product 51 Depth of the product 51 Minimum niche height 0 Minimum niche width 555 Niche depth 475 Net weight (kg) 16 | Number of electric cooking zones | 0 |
| Number of halogen plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Glass Main colour of product Black Electrical connection rating (W) 0 Gas connection rating (W) 10800 Gas type Methane Current (A) 0 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type UK Gas connection N/A Width of the product 730 Height of the product 51 Depth of the product 51 Minimum niche height 0 Minimum niche width 555 Niche depth 475 Net weight (kg) 16 | Number of electric plates | 0 |
| Number of induction plates0Number of electric warming zones0Location of control panelFrontBasic surface materialGlassMain colour of productBlackElectrical connection rating (W)0Gas connection rating (W)10800Gas typeMethaneCurrent (A)0Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)100Plug typeUKGas connectionN/AWidth of the product730Height of the product51Depth of the product510Minimum niche height0Minimum niche width555Niche depth475Net weight (kg)16 | Number of radiant plates | 0 |
| Number of electric warming zones Location of control panel Basic surface material Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type Methane Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Gas connection N/A Width of the product Depth of the product Minimum niche height O Minimum niche width 555 Niche depth Net weight (kg) Front Black Elextrical Glass Methane 0 0 Wethane 100 0 UK 63c connection N/A VIK 50/60 Length of Electrical Supply Cord (cm) 100 Plug type UK 63c connection N/A Width of the product 51 Depth of the product 51 Depth of the product 510 Minimum niche width 555 Niche depth 16 | Number of halogen plates | 0 |
| Location of control panel Basic surface material Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type Methane Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type UK Gas connection N/A Width of the product Depth of the product Minimum niche height No Minimum niche width S55 Niche depth Net weight (kg) Front Glass Front Glass Front Glass Hethack Electrical Connection Methane 0 Methane 200-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 N/A UK Gas connection N/A Width of the product 51 Depth of the product 510 Minimum niche width 555 Niche depth 16 | Number of induction plates | 0 |
| Basic surface material Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type Methane Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type UK Gas connection N/A Width of the product Peight of the product Minimum niche height O Minimum niche width S55 Niche depth Net weight (kg) Gas connection Black Black Black Black Black Black Black Black Black Bl | Number of electric warming zones | 0 |
| Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type Methane Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type UK Gas connection N/A Width of the product Height of the product Depth of the product Minimum niche height O Minimum niche width 555 Niche depth Net weight (kg) Black Black Black | Location of control panel | Front |
| Electrical connection rating (W) Gas connection rating (W) Gas type Methane Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type UK Gas connection N/A Width of the product Table of the product Depth of the product Minimum niche height Net weight (kg) Net Methane O Methane 100 100 100 100 100 N/A Width of the product 51 Depth of the product 51 Net weight (kg) 16 | Basic surface material | Glass |
| Gas connection rating (W) 10800 Gas type Methane Current (A) 0 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type UK Gas connection N/A Width of the product 730 Height of the product 51 Depth of the product 510 Minimum niche height 0 Minimum niche width 555 Niche depth 475 Net weight (kg) 16 | Main colour of product | Black |
| Gas type Methane Current (A) 0 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type UK Gas connection N/A Width of the product 730 Height of the product 51 Depth of the product 510 Minimum niche height 0 Minimum niche width 555 Niche depth 475 Net weight (kg) 16 | Electrical connection rating (W) | 0 |
| Current (A) 0 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type UK Gas connection N/A Width of the product 730 Height of the product 51 Depth of the product 510 Minimum niche height 0 Minimum niche width 555 Niche depth 475 Net weight (kg) 16 | Gas connection rating (W) | 10800 |
| Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type UK Gas connection N/A Width of the product 730 Height of the product 51 Depth of the product 510 Minimum niche height 0 Minimum niche width 555 Niche depth 475 Net weight (kg) 16 | Gas type | Methane |
| Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type UK Gas connection N/A Width of the product 730 Height of the product 51 Depth of the product 510 Minimum niche height 0 Minimum niche width 555 Niche depth 475 Net weight (kg) 16 | Current (A) | 0 |
| Length of Electrical Supply Cord (cm)100Plug typeUKGas connectionN/AWidth of the product730Height of the product51Depth of the product510Minimum niche height0Minimum niche width555Niche depth475Net weight (kg)16 | Voltage (V) | 220-240 |
| Plug type UK Gas connection N/A Width of the product 730 Height of the product 51 Depth of the product 510 Minimum niche height 0 Minimum niche width 555 Niche depth 475 Net weight (kg) 16 | Frequency (Hz) | 50/60 |
| Gas connection N/A Width of the product 730 Height of the product 51 Depth of the product 510 Minimum niche height 0 Minimum niche width 555 Niche depth 475 Net weight (kg) 16 | Length of Electrical Supply Cord (cm) | 100 |
| Width of the product 730 Height of the product 51 Depth of the product 510 Minimum niche height 0 Minimum niche width 555 Niche depth 475 Net weight (kg) 16 | Plug type | UK |
| Height of the product 51 Depth of the product 510 Minimum niche height 0 Minimum niche width 555 Niche depth 475 Net weight (kg) 16 | Gas connection | N/A |
| Depth of the product 510 Minimum niche height 0 Minimum niche width 555 Niche depth 475 Net weight (kg) 16 | Width of the product | 730 |
| Minimum niche height0Minimum niche width555Niche depth475Net weight (kg)16 | Height of the product | 51 |
| Minimum niche width 555 Niche depth 475 Net weight (kg) 16 | Depth of the product | 510 |
| Niche depth 475 Net weight (kg) 16 | Minimum niche height | 0 |
| Net weight (kg) 16 | Minimum niche width | 555 |
| | Niche depth | 475 |
| Automatic programmes No | Net weight (kg) | 16 |
| | Automatic programmes | No |

| TECHNICAL FEATURES | |
|-------------------------|-----------|
| Power on indicator | No |
| Number of indicators | 0 |
| Type of regulation | Semirapid |
| Type of lid | Without |
| Residual heat indicator | Without |
| Main on/off switch | No |
| Safety device | No |
| Timer | No |

| PERFORMANCES | |
|--------------|-----|
| Energy input | Gas |